The final quantity of the tender specification is as revised Below

NIT No. ITPS/Pur/2024-25/24

Dt: 02.07.2024

TECHNICAL SPECIFICATION & PRICE BID/BOQ FORMAT

		PRICE BID FORMAT				
SI.No		MATERIAL DETAILS	QTY.	MON	Unit Basic Price in (Rs.)	TOTAL AMOUNT in (Rs.)
П	DRIVE MOTOR 200KW 200KW Conveyor Drive Motor: • Load : 200KW • FLC: 340A • Efficiency: IE3/IE4 • Duty: S1 • Ingress Protection: IP55 "only IE3/IE4 class for LT Motors"	 Voltage: 415V Speed: 1488 rpm Frame: SE355S Ins. Class: F Mounting: IMB3 (Foot mounted) S" 	1	ON		
2	• Load: 90KW • Load: 90KW • Load: 90KW • FLC: 148A • Speed: 2980 rpm • Frame: 315SMA • Ins. Class: F • Mounting: IMB35 (Foot-cum-flange mounted) "only IE3/IE4 class for LT Motors	•Voltage : 415V •SERVICE FACTOR: 1.22 •Efficiency: IE3/IE4 •Duty: S1 •Ingress Protection: IP55 ange mounted)	1	ON		
m	HT CONVEYOR DRIVE MOTOR • LOAD: 400KW • CURRENT: 85A • ROTOR: COPPER ROTOR • POLE: 4 • DUTY: S1 • INGRESS PROTECTION: IP55 • MOUNTING: IMB3 INCLUSION: PSTB, NPT, 12 Nos RTD PT-100 Simplex 100- Duplex type, 2 Nos Dial type BTD, SPACE HEX Mounting arrangement for vibration probe fixing Columbia to the columbia of the columbia type of the	+ HT CONVEYOR DRIVE MOTOR • LOAD: 400KW • CURRENT: 85A • ROTOR: COPPER ROTOR • POLE: 4 • POLE: 4 • DUTY: S1 • INGRESS PROTECTION: IP55 • MOUNTING: IMB3 INCLUSION: PSTB, NPT, 12 Nos RTD PT-100 Simplex type, 2 Nos BTD PT-100- Duplex type, 2 Nos Dial type BTD, SPACE HEATER & Terminal box, Mounting arrangement for vibration probe fixing.	-	9		
	Only IE3/IE4 Class for H1 Motors	JrS				\neg

NOTE: GST EXTRA AS APPLICABLE (% TO BE INDICATED ALONG WITH HSN CODE).

Other commercial conditions if any, shall be indicated.

All other term and condition of the tender remains the same.

ITPS/Pur/2024-25/24 (dt. 02.07.2024)

Page 10 of 20