

Annexure-II
Material Specification

S/N	DESCRIPTION OF ITEM	QTY	UNIT
A.	SUPPLY PART		
01	Network Video Recorder 64 Channel	2.00	NOS
02	Verifocal Bullet Camera 5MP	75.00	NOS
03	ANPR Camera	4.00	NOS
04	External IR Illuminator	4.00	NOS
05	Hard Disk 8TB Surveillance	16.00	NOS
06	PoE Switch 8 Port Managed	35.00	NOS
07	SFP Managed Switch	2.00	NOS
08	Network Switch 8 Port Managed	2.00	NOS
09	SFP Module	65.00	NOS
10	UPS 6KVA OnLine	1.00	NOS
11	Battery 12V 42AH	16.00	NOS
12	Workstation PC	2.00	NOS
13	LED Screen 75"	2.00	NOS
14	OFC Cable 6 Core	5000.00	MTR
15	HDPE Pipe 32MM	2000.00	MTR
16	Power Cable 1.5sqmm Armored	2000.00	MTR
17	Power Cable 1.5sqmm Unarmored	300.00	MTR
18	Network Rack 17U	1.00	NOS
19	Network Rack 12U	1.00	NOS
20	Network Rack 4U	15.00	NOS
21	Network Rack 4U Outdoor IP 55	15.00	NOS
22	LIU 24 Port	4.00	NOS
23	OFC Distribution Box 6 Port	30.00	NOS
24	CAT 6 Outdoor Cable 305 Mtr Roll	15.00	NOS
25	CCTV Pole GI 20 feet	15.00	NOS
26	OFC Patch Cord SC-LC	65.00	NOS
B.	SERVICE AND INSTALLATION		
01	LAYING OF OFC/POWER CABLE /HDPE/LAN	13000.00	MTR
02	FIXING AND INSTALLATION OF POLE	15.00	NOS
03	FIXING AND INSTALLATION OF CAMERA	79.00	NOS
04	EXCAVATION OF EARTH FOR CABLE LAYING AND RESTORATION OF EXCAVATED SOIL	1000.00	MTR
05	INSTALLATION AND COMMISSIONING NVR, SPLICING OF OFC, INSTALLATION OF NETWORK RACKS, INSTALLATION OF SWITCHES AND ALLIED WORKS TO COMPLETE THE PROJECT	1.00	JOB

DETAILED REQUIRED TECHNICAL SPECIFICATION

1	Network Video Recorder 64 Channel		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Number of Vieo Input Channel : 64		

02	Supported Resolution: 32MP; 24MP; 16MP; 12MP; 8MP; 5MP; 4MP; 1080p		
03	Network Bandwidth: >350 MBPS Incoming and Outgoing		
04	Video Compression : H.265; Smart H.264+; H.264; MJPEG		
05	Video Output: 2 VGA, 2 HDMI, Should Support Simultaneous video source output for VGA and HDMI		
06	Edge Based Video Analytics : Face detection; face recognition; perimeter protection; Smart Motion Detection		
07	Supported Analytics for Camera: Face detection; face recognition; video metadata (human, motor vehicles, and non-motorvehicles); perimeter protection; SMD Plus; stereo analysis; crowd distribution; people counting; ANPR; vehicle density; heat map		
08	Supported Number of Camera for ANPR : 08 Channel or More		
09	Supported Attributes Motor Vehicle : License plate, vehicle body, vehicle Type, Vehicle Colour		
10	Supported Attributes Non Motor Vehicle : Vehicle model, vehicle color, number of persons, helmet		
11	License Plate Database Capacity : minimum 20,000 plate numbers or better		
12	Alarm Input and Output : 16 Channel in; 8 Channel Out		
13	Camera Alarm :Motion detection, Face detection; perimeter protection, Smat Motion Detection, Camera offline; storage error; disk full; IP conflict; MAC conflict; login lockcybersecurity exception		
14	Audio Input and Output : 1 Channel in;2 Channel out		
15	Supported HDD : 8 SATA ports, up to 16TB Each		
16	RAID Supprt : RAID 0/1/5/6/10		
17	Ethernet Interface: 2 x (10/100/1000 Mbps Ethernet port, RJ-45		
18	Interface Port : 4 (2 front USB 2.0 ports, 2 rear USB 3.0 ports), 2 HDMI, 2 VGA, 1 eSATA Port, 1 RS232, 2 RS485 (1 port for half-duplex serial communication, 1 port for full-duplex serial communication)		
19	Supported Protocol : HTTP; HTTPS; TCP/IP; IPv4/IPv6; UDP; SNMP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; PPPoE; FTP; DDNS; Alarm Server; Multicast; InstaOn; Auto Registration; iSCSI, ONVIF 22.06 (Profile T; Profile S; Profile G); CGI; SDK		

20	<p>Compliance & Certification:</p> <p>*OEM should be fulltime member of ONVIF and quoted models should be listed on ONVIF official website (All the certifications & Credentials should be valid on the date of technical evaluation). The CCTV OEM should not be suspended/ blacklisted by ONVIF.</p> <p>*The Bidder/s shall attach the copy of the OEM's ISO Certificate along with the bid. ISO 27001:2013 , IEC27032:2012 & CMMI level 5</p> <p>*The Camera OEM should comply to General Data Protection Regulation (GDPR)</p> <p>*Camera , NVR Should Have ROHS ,BIS CERTIFIED</p>		
21	Approved Make: Honeywell/ Hanwa/ Panasonic/CP PLUS/ HIKVISION/ DLINK		
2	IP Verifocal Bullet Camera		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Required Mega Pixel : 5 Mega Pixel (2592 x 1944)		
02	Image Sensor : 1/2.7" 5MP Progressive scan CMOS		
03	Minimum Illumination: 0.01 Lux@F1.5		
04	Shutter Speed : Auto/Manual, 1/3~1/100000s		
05	Lense : 2.7mm~13.5mm Motorized Lens		
06	AGC : Auto/Manual		
07	Video Compression : H.265/H.264+/H.264/ H.264B/ MJPEG		
08	Angle of View : Horizontal: 100°–26° Vertical: 72°–20° Diagonal: 133°–33°		
09	Back Light Compensation : BLC / HLC / WDR(120dB)		
10	S/n Ratio : More than 50dB		
11	Digital Zoom ; 16x or more		
12	Audio Input and Output : 1 Channel in;1 Channel out; G.711A,G.711Mu,G.726,AAC		
13	Alarm Input and Output : 16 Channel in; 1 Channel Out		
14	Event Trigger/Alarm : Motion detection, Video tampering , Scene changing , Network disconnection, Tripwire, Intrusion		
15	IR RANGE : 60 mtr or more		
16	Ingress Protection: IP 67, Metal Casing		

17	<p>Compliance & Certification:</p> <p>*OEM should be fulltime member of ONVIF and quoted models should be listed on ONVIF official website (All the certifications & Credentials should be valid on the date of technical evaluation). The CCTV OEM should not be suspended/ blacklisted by ONVIF.</p> <p>*The Bidder/s shall attach the copy of the OEM's ISO Certificate along with the bid. ISO 27001:2013 , IEC27032:2012 & CMMI level 5</p> <p>*The Camera OEM should comply to General Data Protection Regulation (GDPR)</p> <p>*Camera , NVR Should Have ROHS ,BIS CERTIFIED</p>		
18	<p>Approved Make: Honeywell/ Hanwa/ Panasonic/CP PLUS/ HIKVISION/ DLINK</p> <p>Camera and NVR</p>		
3	IP ANPR Camera		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Required Mega Pixel : 5 Mega Pixel (2688 × 1520)		
02	Image Sensor : 1/1.8" CMOS		
03	Minimum Illumination: 0.0001 lux		
04	Shutter Speed : Single Shutter		
05	Focal Length : 10mm–50mm Motorized ; Max. F1.33		
06	Field of View : Horizontal: 9.4°–40.8° Vertical: 5.4°–22.9° Diagonal: 10.7°–46.9°		
07	Video Compression: H.265; H.264M; H.264H; MJPEG		
08	Picture Encoding Format : JPEG		
09	WDR : 140db		
10	Signal Processing : Digital Signal Processing		
11	White Balance : Auto; Manual; Outdoor; Natural; Street Lamp; Partial white balance		
12	Inbuilt Storage :1, up to 256 GB; Should Support Automatic Network Replenishment (ANR)		
13	Time Sync: NTP, GPS		
14	Minimum Effective Range of ANPR : 30 Mtr		
15	Minimum Detection Accuracy : 80%		
16	Minimum Speed Detection Range : 0 km/h–120 km/h		
17	Target Vehicle Detection : Motorcycle, Car, Jeep, LMV		
18	Vehicle Type Recognition : Vehicle head: Large bus, heavy truck, medium truck, sedan, van, light truck, medium bus, SUV, MPV, and pickup Vehicle tail: SUV, large bus, sedan, light truck, pickup, medium truck, van, and heavy truck		
19	Alarm Input/Output :2 In/ 2 Out		
20	IR Range : up to 30Mtr		

21	<p>Compliance & Certification:</p> <p>*OEM should be fulltime member of ONVIF and quoted models should be listed on ONVIF official website (All the certifications & Credentials should be valid on the date of technical evaluation). The CCTV OEM should not be suspended/ blacklisted by ONVIF.</p> <p>*The Bidder/s shall attach the copy of the OEM's ISO Certificate along with the bid. ISO 27001:2013 , IEC27032:2012 & CMMI level 5</p> <p>*The Camera OEM should comply to General Data Protection Regulation (GDPR)</p> <p>*Camera , NVR Should Have ROHS ,BIS CERTIFIED</p>		
22	<p>Approved Make: Honeywell/ Hanwa/ Panasonic/CP PLUS/ HIKVISION/ DLINK</p> <p>Camera and NVR should be from same OEM</p>		
4	IR Illuminator		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Suitable IR Illuminator for ANPR Camera o improve performance of the weak light camera, thereby enhancing the picture effects at night.		
02	Material : Aluminium		
03	Beam Angle : 45 Degree or More		
04	IR Range : up to 80 Mtr		
05	Weatherproof Standard: IP67 & IK10		
5	Hard Disk 8TB Surveillance		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Type and Capacity : 8TB SATA 3.5"		
02	RPM : 5400 or Better		
03	Buffer : up to 256MB		
04	Operation Hours (Hours / Day) : 24/7		
05	Suitable for CCTV Surveillance		
06	Apporved Make : Seagate, WD, Toshiba, Samsung, Hitachi		
6	PoE Switch Managed 8 Port		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Number of Ports : 8 x 10/100/1000Base-TX ports + 2 1000Base-X SFP ports		
02	PoE Power Budget: 120 Watt or More		
03	Switching Capacity : 20Gbps or More		

04	Management : Should Support WEB management system, Should Support Local/remote configuration via Telnet, Should Support System configuration with SNMP v1/v2/v3, Should Support Multi-user management		
05	Layer 2 Features : Switching capacity : 20G, MAC address table 8K, Support MAC address table management, MAC Address Binding Support, MAC Address Filtering Support, MAC Address Learning control Control number of port-based MAC address learning		
06	Other Features : Port Control, Port Isolation , Port Self-loop Detection, Port Mirroring Support , VLAN: VLAN Based on Protocol Support IP-Based /MAC-Based VLAN, VLAN Mapping : Support 1:1 mapping		
07	Security Features : Support for MAC-based 802.1X authentication, Support for AAA/RADIUS authentication, Support WEB/Telnet password protection Support Accessing privilege mode password protection, CPU Self-protection		
08	Apporved Make: Dlink, Digisol, Alcatel, Netgear, CP PLUS, TP Link		
7	Managed SFP Switch		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Number of Port : Minimum 8 x 100/1000Base-X + 4x Combo Ports + 4 x Gigabit Ethernet		
02	Switching Capacity : 110 GBPS		
03	Throughput : 80 Mpps		
04	MAC address : 16 K		
05	L1, L2 Features : IEEE802.3(10Base-T), IEEE802.3u(100Base-TX), IEEE802.3z(1000BASE-X), IEEE802.3ab(1000Base-T), IEEE802.3ae(10GBase), IEEE802.3x, IEEE802.3ak(10GBASE-CX4), Port loopback detection, LACP load balance, N:1 Port Mirroring, RSPAN, ERSPAN, 802.1Q, 4K VLAN, MAC VLAN, Voice VLAN, PVLAN, Protocol VLAN, Multicast VLAN, N:1 VLAN Translation, Broadcast / Multicast / Unicast, Port Security Flow Control, Bandwidth Contro		
06	Security : 802.1x AAA, Port, MAC based authentication, Accounting based on time length and traffic, Guest VLAN and auto VLAN, RADIUS for IPv4 and Ipv6		
07	Apporved Make: Dlink, Digisol, Alcatel, Netgear, TP Link, CP PLUS		
8	Managed 8 Port Switch		

S.No	Specification	Compliance (Yes/No)	Remarks
01	Number of Port : Minimum 8 x 10/100/1000MBPS + 2 SFP		
02	Switching Capacity : 40 GBPS		
03	Throughput : 80 Mpps		
04	MAC address : 16 K		
05	L1, L2 Features : IEEE802.3(10Base-T), IEEE802.3u(100Base-TX), IEEE802.3z(1000BASE-X), IEEE802.3ab(1000Base-T), IEEE802.3ae(10GBase), IEEE802.3x, IEEE802.3ak(10GBASE-CX4), Port loopback detection, LACP load balance, N:1 Port Mirroring, RSPAN, ERSPAN, 802.1Q, 4K VLAN, MAC VLAN, Voice VLAN, PVLAN, Protocol VLAN, Multicast VLAN, N:1 VLAN Translation, Broadcast / Multicast / Unicast, Port Security Flow Control, Bandwidth Contro		
06	Security : 802.1x AAA, Port, MAC based authentication, Accounting based on time length and traffic, Guest VLAN and auto VLAN, RADIUS for IPv4 and Ipv6		
07	Apporved Make: Dlink, Digisol, Alcatel, Netgear, TP Link, CP PLUS		
9	TRANCEIVER /OFC Module		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Wave Length: 1310nm		
02	Data Rate: 1Gbps		
03	Supported Cable Length : 10KM or More		
04	Transceiver Type : SFP (Small Form Pluggable)		
05	Connector : LC Type		
06	Apporved Make: Cisco, Dlink, Digisol, Alcatel, Netgear, HP Aruba, TP Link, CP Plus		
10	UPS 6KVA Online		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Required Capacity : 6000 VA / 4800 W		
02	Technology : Switch Mode rectifiers/Phase Controlled Rectifiers/IGBT		
03	Primary Source Voltage: Single Phase, 230 V AC		
04	Output Characteristics : Constant Voltage/ Constant Current		
05	Protection Advanced Electronic protection for device safety backed up with MCBs/MCCBc and fast acting fuses, Soft start for 0-20 Sec, power walk-in		
06	Input Power Factor >0.95 with Harmonic suppression		
07	Output Technology : Digital SMWM IGBT Design		
08	Output Voltage : 230 VAC (1 Phase)		

09	Output Frequency : 50 Hz (+/- 0.1%)		
10	Harmonic Distortion : THD<2% for linear loads, <5% for non-linear loads		
11	Transient Response For 100% step load change, +/- 5% and recovers to normal with in 60 milliseconds		
12	Overload : 110% for minimum 30 Seconds		
13	Indications: Mains On, DC ON, Output ON, Converter Fault, Low DC, Inverter Trip, Output High, Output Low, Bypass Mode, Battery Mode.		
14	LCD Display Parameter UPS status, Load level, Battery level, Input/Output voltage, Discharge timer, and Fault conditions		
15	Power Distribution Panel: To be supplied along with UPS		
16	Approved Make : APC/Emersion/Delta Electronics/Hitachi Numeric/Vertive/ Luminous/ Microtek/Eaton		
11	Battery SMF for UPS		
S.No	Specification	Compliance (Yes/No)	Remarks
01	General Specification : Battrey Voltage : 12 Volt Battery Capacity : 42 Ah Battery Type : SMF / VRLA Batteries		
02	Approved Make : Exide/Amaraja/Quanta/TATA		
12	Work Station PC		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Form Factor: Tower Type Desktop		
02	Processor : Intel Core i-7 Processor, 8 Cores/12MB/6T/up to 4.0GHz/65W or Better		
03	Memory : 16 GB 3200MHz or Higher		
04	Graphics : 4GB Dedicated Graphics		
05	Storage : 512GB SSD		
06	I/O Ports :USB : 6, (4 back and 2 Front), Universal Audio Jack, VGA/Display Port and HDMI Port, 1 RJ - 45		
07	Monitor : 24" HD LED		
08	Software : Microsoft Windows 11 Pro Factory Installed		
09	Accessories : Keyboard, Mouse, Cable and Connectors		
10	Approved Make: Dell/HP/Lenovo/ACER/Fijitsu /HCL		
13	LED SCREEN 75"		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Panel/Screen Size : 75" Diagnol		
02	Panel Type : IPS		

03	Resolution : 3840 ×2160 or Better		
04	Brightness : 500nits or Higher		
05	Contrast Ratio : 1,100 : 1 or Higher		
06	Viewing Angle (H ×V) : 178 ×178		
07	Operation Hours (Hours / Day) : Offered Screen Must bedesigned for 24/7 operational Hrs.		
08	Mounting Angle : Portrait and Landscape		
09	Input Ports : 3x HDMI, 1xDP, 1xDVI-D, 1xUSB, 1x RJ-45 Ethernet, 1xRS232,		
10	Output Port : 1xDP, 1xAudio		
11	Software Compatibility : Inbuilt Signage Player, Signage Controler		
12	Internal Memory : 8 GB or More		
13	WiFi: Inbuilt		
14	Mounting optition : Wall Mountable, VESA Mount		
15	Certification : FCC, Energy Star 8.0, CB, NRTL		
16	Apporved Make : LG, Samsung, Sony, Panasonic, Delta Electronics, Barco		
14	OFC Cable 6 Core Single Mode Armored		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Number of Core : 6 Core Single Mode Armored		
02	Fiber-Type : 9/125 / G.652D 1.4674/1.4679		
03	Outer Dia : 9mm +/- .03 or better		
04	Thikness of Jacket : 1.8mm +/-0.2 HDPE		
05	Wavelength Supported : 1310/1550		
06	Operating Temp : -40°C to 60°C		
07	Nominal Cable Weight (kg/km) : 65 KG		
09	Tensile Strengt : 1000N		
10	Crush Load (N/100mm) : 2000		
11	Armouring : Corrugated Steel Tape		
12	Water Blocking Compound : Flooding Jelly		
13	Application : Cable Suitable for Outdoor network System Bidder will have to produce test certificate from the manufacturer at the time of supply		
14	Apporved Make : Finolex, Polycab, Dlink, AMP, Digisol, Molex		
15	HDPE Pipe		
S.No	Specification	Compliance (Yes/No)	Remarks
01	General Specification : The HDPE pipe used shall have minimum outer diameter of 32mm and 2 mm thickness and should be supplied in roll of minimum 200 meters or more		
16	Power Cable 1.5 Sqmm Armored		
S.No	Specification	Compliance (Yes/No)	Remarks

01	Type of Cable : 3 Core x 1.5 sq mm LT Industrial Armored Cable		
02	Conductor Material : Copper		
03	Voltage Rating : 1.1 KV		
04	Conductor Construction: 1.5 sq mm Single stranded annealed bare electrolytic grade, conductor resistance <7.5 Ohms/km		
05	Primary Insulation: Extruded PVC compound as per IS 5831 type C		
06	Outer Sheath : FRLS		
07	Armour over inner sheath Thickness >1.2mm		
09	Core Identification : 3 cores Red, Black & Blue/Green		
10	Appored Make : HAVELLS , POLYCAB, FINOLEX , DELTON, KEI		
17	Power Cable 1.5 Sqmm Un-Armored		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Type of Cable : 3 Core x 1.5 sq mm Flexible Unarmored		
02	Conductor Material : Copper		
03	Voltage : 1.1 KV		
04	Conductor Construction: 1.5 sq mm Multi stranded annealed bare electrolytic grade, conductor resistance <7.5 Ohms/km		
05	Insulation:FRLS		
06	Core Identification : 3 cores Red, Black & Blue/Green		
07	Appored Make : HAVELLS , POLYCAB, FINOLEX , DELTON, KEI		
18	Network Rack 17U		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Number of Unit Racks: 17U		
02	Rack Width: 19 inches		
03	Body Material: Welded		
04	Usable Depth: 600mm		
05	Usable Height: 675MM or Better		
06	Load Capacity: 25 KG		
07	Door Type: Lockable Toughened Glass		
08	Finish Powder Coated		
09	Additional Features: Including of FAN, PDU and Cable Manager		
10	Rack Standard: Conforms to DIN 41494 or equivalent standard		
11	Approved Make: Dlink/I-BALL/NETRACK/WALL RACK/APC/CP Plus		

19 Network Rack 12U -Wall Mount			
S.No	Specification	Compliance (Yes/No)	Remarks
01	Number of Unit Racks: 12		
02	Rack Width: 19 inches		
03	Body Material: Welded		
04	Usable Depth: 430mm or More		
05	Usable Height: 550MM or More		
06	Load Capacity: 25 KG		
07	Door Type: Lockable Toughened Glass		
08	Finish Powder Coated		
09	Additional Features: Including of FAN, PDU and Cable Manager		
10	Rack Standard: Conforms to DIN 41494 or equivalent standard		
11	Approved Make: Dlink/I-BALL/NETRACK/WALL RACK/APC/CP Plus		
20 Network Rack 4U -Wall Mount			
S.No	Specification	Compliance (Yes/No)	Remarks
01	Number of Unit Racks: 4U		
02	Rack Width: 19 inches		
03	Body Material: Welded		
04	Usable Depth: 350mm		
05	Usable Height: 240MM		
06	Load Capacity: 25 KG		
07	Door Type: Lockable Toughened Glass		
08	Finish Powder Coated		
09	Additional Features: Including of FAN, PDU and Cable Manager		
10	Rack Standard: Conforms to DIN 41494 or equivalent standard		
11	Approved Make: Dlink/I-BALL/NETRACK/WALL RACK/APC/CP Plus		
21 Network Rack 4U Outdoor IP 55			
S.No	Specification	Compliance (Yes/No)	Remarks
01	Number of Unit Racks: 4U		
02	Rack Width: 19 inches		
03	Body Material: Welded		
04	Usable Depth: 350mm		
05	Usable Height: 240MM		
06	Load Capacity: 25 KG		
07	Door Type: Hinged Lockable Metal Door		
08	Finish: Powder Coated		
09	Additional Features: Including of FAN, PDU, Rack Shoulf have proper Ventilation with air filter		
10	Rack Sould be IP 55 Rated (Dust proof, Rust proof & Rain water protected).		

11	Approved Make: Dlink/I-BALL/NETRACK/WALL RACK/APC/CP Plus		
22	LIU 24 Port		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Mounting : 19" Rack mountable or suitable size to mount on Rack		
02	Copler/Connectors : Couplers 24 no SC Single Mode couplers with Coupler Plate(If Required)		
03	Pigtel : Suitable Pigtel with SC Connectors		
04	Apporved Make : Molex, Dlink, Digisol, Syrotech, AMP, Tyco		
23	OFC Termination Box		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Suitable to Accomodate 6 Core Fiber, Must Contain splicing connectors, fiber optic field connectors, Having 2 or more Cable Entry Hole. OFC Termination Box is to use in each Camera location. With Each Junction Box. 2-4 Core Fiber will be left in Camera JB and Rest Core will be extended to the next Camera JB		
24	CAT 6 Outdoor Cable		
S.No	Specification	Compliance (Yes/No)	Remarks
01	Conductor : 4 Pair, 23 AWG, Solid bare copper		
02	Insulation Material : High density polyethylene (HDPE)		
03	Shielding : Aluminium/Polyster Foil		
04	Overall Sheath : Tinned Copper Braiding		
05	Jacket : FRPVC/LSZH sheath		
06	Maximum Tensile Strength of Jacket (N/mm ²) : 13		
07	Pulling Force : 25 LBS		
08	Bending Radius : < 8X Cable Diameter at -20°C +/- 1°C		
09	Operating Temperature : -20°C to +70°C		
10	Impedance : 100 ± 15 Ω @ 100 Mhz		
11	Current Rating : 1.5 A Max.		
12	Operating Voltage : 72v		
13	Standard Length of Roll : 305 Mtr		
14	Standard/Certifications: UL Listed, ETL Verified to ANSI/TIA-568-C.2, ISO/IEC 11801, RoHS Compliant		
15	Apporved Make : Finolex, Polycab, Dlink, AMP, Digisol, Molex,CP PLUS		
25	Pole 6 Mtr GI		
S.No	Specification	Compliance (Yes/No)	Remarks

01	GI Pole Length : 6 Mtr, OD 5" or More, Suitbale for Camera. Base/Mounting Plate : Minimum 6 MM in Thickness, size 10"x10" with 4 NosSuitable Size of Hole for Pole Mounting. Must have provision of Cable Entry Holes		
26	OFC Patch Cord SC-LC		
S.No	Specification	Compliance (Yes/No)	Remarks
01	OFC Patch Cord SC-LC Duplex, Single Mode, Length 3 Mtr		
02	Apporved Make : Molex, Dlink, Digisol, Syrotech, AMP, Tyco		